

# Fall Protection



# Fall Protection

XXXX

EXOFIT™ 1100300 / DELTATM 1102008



**Features:**

- Built-in shoulder, back and leg comfort padding
- 18" back D-ring extension
- Body belt/hip pad with back D-ring
- Seat sling with positioning D-rings
- Integrated derrick belt connection (shown with)
- Quick connect chest strap
- Tongue buckle leg straps
- Soft, lightweight webbing
- Anti-tear ballistic nylon
- Built-in reflective piping
- Parachute torso adjusters

XXXX

## Lanyards & Accessories



ShockWave™ 2 100% TieOff Shock Absorbing Lanyard. Model: 1244412

EZStop™ 100% TieOff Shock Absorbing Lanyard. Model: 1246029

Tagline for Self Retracting Lifeline. Model: 7211856



Rescue/Retrieval Y-Lanyard with Spreader Bar. Model: 1234160



Saflok™ Carabiner. Model: 2000114 & 2000112

**Model 1244412:**

- 6 ft. (1.8m) double-leg 100% tie-off lanyard
- Stretches in reaction to your movements

**Model 1246029:**

- 4 ft. (1.2m) double-leg 100% tie-off lanyard
- Extremely compact and lightweight

**Model 7211856:**

- Tagline for self retracting lifeline
- 50 ft. (15 m) 3/16" (5 mm) polypropylene rope
- Attached steel O-ring

**Model 1234160:**

- 2 ft. (0.6 m) rescue/retrieval Y-Lanyard
- Keeps victim upright during rescue

**Model 2000114 & 2000112:**

- 2-3/16 in. (55.5mm) gate opening steel carabiner
- Self closing and locking gate for added safety

### AG399

3M | DBI-SALA SALAlift II Winch, 60 ft. Galvanized Steel Cable 8102001



#### Features:

- installType:Portable
- LifelineMaterial:1/4 in. (6.3 mm) Galvanized Steel Wire Rope
- (LifelineLength:60 ft. (18 m)
- (Weight:38lbs. (17.2 kg
- (Capacity:350lbs. (159 kg
- SALaliftII winch with 60 ft. (18 m) of 1/4 in. (6.3 mm) galvanized steel wire rope and swivel snap hook, mounting bracket and carrying bag
- GearRatio Mechanical Advantage - Easy operation, gear ratio 6:1 is 6:1 with an average lifting speed of 0.06 m/sec
- FreeWheel Mode - allows the drum to rotate and cable to pay-out freely as the attached worker descends or moves about
- Built-In Overload Clutch - automatically slips to prevent severe overloading or damage; it also helps prevent injury to entangled personnel during raising operation

### 8301031

ADVANCED TM ALUMINUM TRIPOD WITH SEALED BLOK TM 3WAY SRL



#### Features:

- 7 ft. (2.1 m) aluminum tripod (model 8000000)
- Telescoping adjustable locking legs
- Built-in pulley system
- Specialized safety shoes and leg support chain
- Integrated 5,000 lb. (22 kN) eyebolt anchor points
- Environmentally sealed self retracting lifeline (model 3400924)
- 3-way emergency retrieval system
- Crank handle has built-in brake
- Built-in winch drive overload device
- 50 ft. (15m) 3/16" (5mm) stainless steel cable lifeline
- Reserve lifeline system
- Swiveling snap hook with impact indicator
- Quick connect winch/SRL mount bracket
- Equipped with i-SafeTM



3M DBI-SALA Sealed-Blok 3400932 Self Retracting/Rescue Dual Mode Lifeline, 50-Foot, 3/16-Inch SS Wire, Swivel Snap Hook, Carabiner, 4-Foot Cable Tie-Off Adaptor, Yellow

#### Features:

- Environmentally sealed dynamic components
- Extremely durable construction
- Anti-ratcheting locking system
- Built-in carrying handle
- 50 ft (15m) of 3/16" (5mm) stainless steel wire rope with swivel snap hook, RSQ dual-mode, anchorage carabiner, 4 ft (12m) cable tie-off adaptor
- For industrial/occupational use only